



Extreme Versatility, High Powered Mobility

NEAL DUAL APPLICATORS combine two powerful means of applying sealer in one highly mobile self-propelled unit. Equipped with the ESSP pumping system and dual drag squeegee assembly, the DA-350 is both extremely versatile and easy to maneuver. Hydrostatic rear wheel drive offers high traction and tight turning capabilities for difficult job conditions. Power steering offers smooth operation for quick turns. The dual drag squeegee assembly offers complete and easy operator control over material distribution. Foot pedals provide on-demand control of the 4" material drop, releasing material directly into the squeegee box. The window operator arm allows further manipulation of how the material is applied to the surface.

For spray application nothing out-performs a Neal ESSP spray system. The 100 gpm hydraulically driven piston pump with our Generation III pump head means uninterrupted pumping power with no downtime. The DA-350 dual applicator is your choice for high versatility on all job sizes and specs. Call us or visit our web site for more information.

DA-350 Specifications

MODEL/ capacity	overall length	overall width	overall height	weight (lbs.)	engine HP	fogger system
350	167"	67"	78"	3,400	35 diesel	40 gal.

- Hydrostatic rear wheel drive for optimum traction on the job and easy loading
- Low profile engine deck and 20.75" tires for increased stability and operator visibility
- Hydraulic Joystick for positive control
- Spring applied / hydraulic released parking brake
- Unloading valve on auxiliary pump for easy engine starting
- ESSP 100 gallon per minute piston pump
- Generation III pump head controller utilizing time proven Neal technology
- Powered by 35 hp Kubota Diesel Engine
- Optional hydraulic spray bar