

Pavement Maintenance Equipment

HDP Trailer Systems

High Mobility and Superior Efficiency

OVER THE YEARS Neal spray applicators have proven to be the high performance standard for professional contractors world-wide. Their rugged build and low maintenance, combined with the high volume pumping power of a Neal HDP piston pump, make them the clear system of choice. HDP Trailers deliver the power of a Neal system to and from your job site safely and efficiently. Highly maneuverable, HDP 550 and 750 Trailers are ideal for small driveways to mid-sized parking lots. The optional distributor bar and second hand wand transform HDP Trailers into super high volume sealcoat applicators for enhanced efficiency and higher production. Generation 4 pump head technology, 2.5 gallon material filters and Kohler Command Pro[™] engines, all ensure peak job site performance with Neal.

HDP Trailer Features...

- Proven Neal 100 gpm Hydraulic Piston Pump
- Robust Tubular Steel Framework
- Dual 7,000 lb.Axles
- 24 gal. Poly Water Tank
- Reliable 19 HP Kohler Command Pro[™] with Electric Start
- LED Running Lights
- Extended Deck
- Locking Hood
- Safety Breakaway Switch
- Hand Wand Water Tank Holder

HDP Trailer Systems

Specifications



HDP Trailer Power Options

• 19 HP Kohler Command Pro[™] Gasoline Engine

OPTIONS

- Spray Bar and Spray Bar Extensions
- HDP 50 GPM Piston Pump
- 2nd Hose and Hand Wand
- Hose Reel
- Operator Seat
- 15 ft. Suction Hose
- Brush Box

NEAL HDP PUMP BENEFITS

- Proven Neal 100 gpm Hydraulic Piston Pump
- Generation 4 Pump Controller
- Designed for Heavily Sanded Materials
- Low Maintenance
- Flush Once Per Year

PUMP PERFORMANCE

- Maximum Volume 100 gpm
- Maximum Pressure 130 psi



Neal HDP Hydraulic Piston Pump



EPA Approved Fuel Tank

HDP 550/750 T Dimensions

MODEL	length	width	height	weight	capacity	brakes	axles (g.v.w.)
750 T	226''	76''	80''	4,260 lbs.	750 gal.	electric	12,000 lbs.
550 T	202''	76''	80"	4,000 lbs.	550 gal.	electric	12,000 lbs.

HDP Trailer Technical Info

- Capacity Avaliable-550 or 750 gal.
- Hand Wand- 6 ft. Wand with 75 ft. Delivery Hose
- 2.5 gal. Material Filter
- 25 gal. Water Cleaning System Including Water Pump
- 3/16" Steel Tank Construction
- 1.5" Solid Agitator Shaft
- Variable Speed Mixing with Forward/Stop/Reverse
- Du
- Tra
- EPA Approved 10 gal. Fuel Tank
- Tubular Steel Framework

NEAL Parts & Service

The most reliable customer support team in the industry offering next day air shipments for the Neal product line.



Trailer Breakaway Kit and Adjustable Hitch



2.5 gallon material filter for extended spray periods



In-line surge tank never needs cleaning



Call: 770.830.1282 www.nealequip.com

2000 Cobb Ave., Anniston, Alabama 36201 • FAX: 256.236.9824 • EMAIL: info@nealequip.com

© 2015 Neal Manufacturing Company, A Division of Blastcrete Equipment Company • All rights reserved • Specifications may change without notice.

1 0									
ual 7,000 lb. Axles									
ailer Safety Breakaway Kit									
A Approved 10 gal FuelTank									